

PacifiCorp

Updated May 28, 2025

These EVSE meet the program requirements established by PacifiCorp. All hardware must have a minimum 3-year warranty.

All qualifying EVSE hardware must be paired with an approved third-party network service.

Residential (AC Only; 6kW to 12kW)

Brand	Model	Model Name	Type	Max Power (kW)	Notes
ATG Electronics	ATG-C01-40A	Commercial EV Charger	AC	9.6	Single port
ATG Electronics	ATG-C01-48A	Commercial EV Charger	AC	11.5	Single port
Atom Power	Purpl 48A	Purpl 48A	AC	11.5	
Autel	AC W12-L-4G	AC Elite	AC	12	Single Port ; OCPP Full Certificate with software version V1.13.97
Autel	MAXI US AC LW12	AC Lite	AC	12	Single port. NEMA 14-50 plug. Separate holster.
Autel	MAXI US AC W12	AC Elite Home	AC	12	Single port. NEMA 14-50 plug. Separate holster.
Autel	MAXI US AC W12-H	AC Elite Home	AC	12	Single port. NEMA 14-50 plug. Separate holster.
Autel	UW12-J0610CA0002	MaxiCharger AC Single	AC	12	Single port.
Autel	UW12-J0650CA0002	MaxiCharger AC Single	AC	12	Single port.
Blink	01-0202 (MQ 200)	MQ 200	AC	12	Single Port; NRTL listed as LiteOn MQW2-50C-M2-R#-#-23 and HQW2-50C-#-N#-#-23
Blink	780 (40A)	Series 7 ISO (Enhanced)	AC	9.6	Dual Port, Standalone network capability
Blink	780 (48A)	Series 7 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability
Blink	880 (40A)	Series 8 ISO (Enhanced)	AC	9.6	Single or dual Port, Standalone network capability
Blink	880 (48A)	Series 8 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability
Blink	IQW2-80U-M3-R3-N-25-40 (Advanced LTE- W)	IQ 200 Advanced	AC	8.3	Single Port
breezEV	EVC-L2-48A-L1-1-4G-D-AU-L-#	SMART CONNECTED LEVEL 2 EV CHARGING STATION	AC	11.2	48A Max Charger, Screen, RFID, 4G Cellular, Wall-Mount, AmpUp LITE Plan, # determines plan length
BTC Power	EVP-2001-30-#		AC	7.2	Single Port, Must acquire Gateway for network connectivity
BTC Power	EVP-2001-40-#		AC	7.2	Single Port, Must acquire Gateway for network connectivity
ChargePoint	CP6###X-50A-L##	6000 Series	AC	12	CP6000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 50A or 80A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 8" Touch Display, Contactless Credit Card and RFID Reader, Cellular/Wi-Fi, UL, Power Share Jumper, 1YR Parts Warranty, Optional credit card reader
ChargePoint	CPF50- L##-*****	CPF50	AC	12	CPF50 family, Single or Dual Port, Pedestal or Wall Mount, 50A, Type 1, Cable 18' or 23', Single Phase Charger, Cable Management Kit optional
ChargePoint	CT40##-GW1L-*****##	CT4000	AC	7.2	CT4000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 30A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 5.7" Display, Contactless Credit Card and RFID Reader
ChargeTronix	UP160J-#MP-###	UP160J	AC	7.2	Dual Port, Must acquire Gateway for network connectivity
ChargeTronix	UP80J-#MP-###	UP80J	AC	7.2	Single Port, Must acquire Gateway for network connectivity
Chargie	CH-L-48-PRA-1-18		AC	11.52	
Chargie	CH-L-48-PRA-1-18-32		AC	7.68	
Chargie	CH-L-48-PRA-1-18-40		AC	9.6	
Chargie	CH-L-48-PRA-1-25		AC	11.52	
Chargie	CH-L-48-PRA-1-25-32		AC	7.68	
Chargie	CH-L-48-PRA-1-25-40		AC	9.6	
Chargie	CH-L-48-PRAC-1-18		AC	11.52	
Chargie	CH-L-48-PRAC-1-18-32		AC	7.68	
Chargie	CH-L-48-PRAC-1-18-40		AC	9.6	
Chargie	CH-L-48-PRAC-1-25		AC	11.52	
Chargie	CH-L-48-PRAC-1-25-32		AC	7.68	
Chargie	CH-L-48-PRAC-1-25-40		AC	9.6	
Chargie	CH-L-48-PRACT-1-18		AC	11.52	
Chargie	CH-L-48-PRACT-1-18-32		AC	7.68	
Chargie	CH-L-48-PRACT-1-18-40		AC	9.6	
Chargie	CH-L-48-PRACT-1-25		AC	11.52	
Chargie	CH-L-48-PRACT-1-25-32		AC	7.68	
Chargie	CH-L-48-PRACT-1-25-40		AC	9.6	
Chargie	CH-L-48-PRAT-1-18		AC	11.52	
Chargie	CH-L-48-PRAT-1-18-32		AC	7.68	
Chargie	CH-L-48-PRAT-1-18-40		AC	9.6	
Chargie	CH-L-48-PRAT-1-25		AC	11.52	
Chargie	CH-L-48-PRAT-1-25-32		AC	7.68	
Chargie	CH-L-48-PRAT-1-25-40		AC	9.6	
Cyber Switching	CSE1-4G-BL	CSE1	AC	11.5	Single Port
Cyber Switching	CSE1-WIFI-BL	CSE1	AC	11.5	Single Port
Eaton	GMEV32BAB-DC / GMEV32BR-DC / GN	Green Motion EV Charger	AC	7.7	
Eaton	GMEV40CIE1B-WC/GMEV40CIC1B-WC	Green Motion EV Charger	AC	9.6	
Eaton	GMEV40CME1B-WC/GMEV40CMC1B-WC	Green Motion EV Charger	AC	9.6	
Eaton	GMEV48CMC1-WC	Green Motion Building Pro	AC	11.5	Single port.
Eaton	GMEV48CME1-WC	Green Motion Building Pro	AC	11.5	Single port.

Emporia	EMEVE1	EV Charger	AC	11.52	
EnergiSpot	ATLEU2-50AAS	Level 2 AC Charger	AC	12	Single port per unit, when configured as a dual unit on a single pedestal, each charger delivers their perscribed max output rating - never splitting power on a simultaneous charging session.
EnergiSpot	ATLUE2-32AAS	Level 2 AC Charger	AC	7.7	Single port per unit, when configured as a dual unit on a single pedestal, each charger delivers their perscribed max output rating - never splitting power on a simultaneous charging session.
Enphase	HCS-40	EV Charger	AC	7.7	Single port, Must acquire Gateway for network connectivity
Enphase	HCS-50	EV Charger	AC	9.6	Single port, Must acquire Gateway for network connectivity
Enphase	HCS-60	EV Charger	AC	11.5	Single port, Must acquire Gateway for network connectivity
Enphase	Zeal-32A	HCS-40	AC	7.7	Single port, Must acquire Gateway for network connectivity
Epic Charging	EC48-AC	Epic48	AC	11.5	Single Port, Standalone network capability
Epic Charging	ECB48-AC	Epic48	AC	11.5	Single Port, Standalone network capability
Espen	EVC/A48S	EVC/A48S	AC	11.5	Single port.
Espen	EVC/A48SX2	EVC/A48SX2	AC	11.5	Dual Port
EVBox	Iqon IQ2303-#####	Iqon	AC	7.2	Dual Port , Standalone network capability
EverCharge	EV002-48,E800-1000	EV02	AC	11.52	Single Port, Standalone network capability
EverCharge	EV002-48,E800-1000-40A	EV02	AC	8.3	Single Port, Standalone network capability
EverCharge	EV002-80,E800-1001-40A	EV02	AC	8.3	Single Port, Standalone network capability
EVGateway	EGW-#C-32-#		AC	7.7	
EVGateway	EGW-#C-40-#		AC	9.6	
EVGateway	EGW-#C-48-#		AC	11.5	
EVmode	EVM2000-EVM101U	EVM2000	AC	11.5	Single port.
EvoCharge	EVC5001####	EVC5001####	AC	12	Single port.
EvoCharge	EVO32-310-001	iEVSE Plus 32	AC	7.7	Single Port, Standalone network capability
EvoCharge	EVO32-310-002	iEVSE Plus 32	AC	7.7	Dual Port, Standalone network capability
EvoCharge	EVO32-320-001	iEVSE 32	AC	7.7	Single Port, Standalone network capability
EvoCharge	EVO32-320-002	iEVSE 32	AC	7.7	Dual Port, Standalone network capability
EvoCharge	W1-1962-####	iEVSE	AC	9.6	
EVPassport	Ezra Charger	Ezra	AC	7.7	Single Port, Standalone network capability
EVPassport	Rosa Charger	Rosa	AC	11	NRTL listed as Phihong AWLU770001
EVSE LLC	3703	ChargeWorks EV Charger	AC	9.6	Single port, Must acquire Gateway for network connectivity
EVSE LLC	3722	EVSE Garage Overhead Charger	AC	9.6	Single port, Must acquire Gateway for network connectivity
EVSE LLC	3704 REV G	AutoCoil EV Charger	AC	9.6	Single port, Must acquire Gateway for network connectivity
EVSE LLC	3704-002 REV G	AutoCoil EV Charger	AC	9.6	Single port, Must acquire Gateway for network connectivity
FLO	CoRe+ STD 21 FT	CoRe+™	AC	7.2	Dual Port , Standalone network capability
FLO	SmartTWO	SmartTWO™ Series	AC	7.2	Single Port, Standalone network capability
FLO	SmartTWO Cellular	SmartTWO™ Series	AC	7.2	Single Port, Standalone network capability
FLO	SmartTWO For City Curbside	SmartTWO™ Series	AC	7.2	Single Port, Standalone network capability
Ford Pro Charge	FPC-AC0048ZC-###	Ford Pro AC Charging Station, 48A Seri	AC	11.5	Single Port.
Ford Pro Charge	FPC-AC0011ZC-U##		AC	11.5	Single Port
FractalEV	FR482C1DRNAJ	FR48	AC	11.5	NRTL listed as Siemens 8EM1314-5CG14-2FA2
Free2Move	E21CA180Dx		AC	11	Single port
Free2Move	E21CH012##		AC	11	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
InCharge	ICE-40 AC	ICE-40 AC	AC	9.6	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
Integra Energy	IEV-48SEL	IEV-48SEL	AC	11.5	40 A 9.6 kW
					Single port.
IoTecha	CCS-ACL2-40 / CCS-C40A	CCS-ACL2-40 / CCS-C40A	AC	8.3	Single Port. xx - cable length (15 or 25ft) yyy - LTE option
Legrand	LNA-EVC1-48-SV1	Networked Level 2 Commercial EV Cha	AC	11.5	
Lenz	EVSE W1 40 A		AC	9.6	
LITE-ON	AC7LC	AC7LC	AC	7	
LITE-ON	W1-UC168-0MF1F0	SC48A	AC	11.52	Single port.
LITE-ON	W1-UC168-0MF1F0	ADV 48A	AC	11.52	Single port.
LITE-ON	W1-UC168-0MF1FR	ADV+ 48A	AC	11.52	Single port.
LITE-ON	W1-UC168-0MJ1EP	ADV+ 48A POS	AC	11.52	Single port.
LITE-ON	W1-UC168-0MK1ER	IC 48A	AC	11.52	Single port.
LITE-ON	W1-UC168-0ML1EP	IC 48A POS	AC	11.52	Single port.
Loop Global	EVS-32A-L2-001	EV-Flex LITE	AC	7.68	SAE J1772, Standalone network capability
Loop Global	EVS-32A-L2-002	EV-Flex LITE	AC	7.68	SAE J1772, Standalone network capability
Lynkwell	LW141-AC50	LW141-AC50	AC	12	Single Port ; OCPP Full Certificate with software version V1.13.97
Lynkwell	LW201-AC32	LW201-AC32	AC	7.6	
Noodoe	AC11P/AC11P Exceed		AC	11.5	Single port.
OpConnect	OC-IC3-32AH		AC	7.2	Single port.
OpConnect	OC-SC3-32AN		AC	7.7	Single Port, Standalone network capability
PowerFlex Syst	JNT-EVC10 (PF-JT48)		AC	11.52	Single Port, Standalone network capability
PowerFlex Syst	W1-UC168-0MF1FR	ADV+48A / SC48	AC	11.6	Must acquire Nexus
PowerFlex Syst	W1-UC168-0MK1ER	IC 48A	AC	11.6	Single port.
PowerFlex Syst	W1-UC168-0ML1EP	IC 48A with POS	AC	11.6	Single port.
PowerPump	AC550	AC550	AC	10	Single port.
RAB Lighting In	EVC48	EVC48	AC	11	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
Siemens	8EM13105HF141GA2	VersiCharge AC 48A NTEP	AC	11.5	Single Port, Standalone network capability
Siemens	8EM13155HG141GA2	VersiCharge Blue AC 48A NTEP	AC	11.5	Single Port, Standalone network capability
Siemens	VersiCharge 11.5kW8EM1310-5CF14-0	VersiCharge	AC	11.5	Single Port, Standalone network capability
Siemens	VersiCharge 11.5kW8EM1310-5CF14-1	VersiCharge	AC	11.5	Single Port, Standalone network capability
Siemens	VersiCharge 11.5kW8EM1312-5CF18-0	VersiCharge	AC	11.5	Single Port, Standalone network capability
Siemens	VersiCharge 9.6kW8EM1310-4CF14-0	VersiCharge	AC	9.6	Single Port, Standalone network capability

Siemens	VersiCharge 9.6kW8EM1310-4CF14-1C	VersiCharge	AC	9.6	Single Port, Standalone network capability
Siemens	VersiCharge 9.6kW8EM1312-4CF18-0F	VersiCharge	AC	9.6	Single Port, Standalone network capability
SWTCH Energy	AXLU111001/48	AX48	AC	11	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
SWTCH Energy	IC3-32A-H-A	SWTCH Lite-On Platinum IC3	AC	7.6	Single Port NRTL Listed as IC3-32A-H-A
SWTCH Energy	SC3-32A-H	SWTCH Lite-On Platinum SC3	AC	7.6	Single Port NRTL Listed as SC3-21A-H
TECO-Westingh	AWLU770001/AW32		AC	7.7	Single Port, Standalone network capability
Tellus Power	UP160J-#MP-###		AC	7.2	Dual Port, Must acquire Gateway for network connectivity
Tellus Power	UP80J-#MP-###		AC	7.2	Single Port, Must acquire Gateway for network connectivity
TurnOnGreen	EVP1100-W/CPEVAC-11KW-J17-WEVP		AC	11.4	Single Port
TurnOnGreen	EVP700-W/CPEVAC-7KW-J17-W/EVP7		AC	7.6	Single Port
Wallbox	PUP1-#-1-5-#-### / PUP2-#-1-5-#-###	Pulsar Plus	AC	9.6	Single Port
Zerova	AWLU770001/AW32	ICS AWG 4G	AC	7.7	Single Port, Standalone network capability
Zerova	AXLU111001/AX48	AX48	AC	11	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00

Commercial

Brand	Model	Model Name	Type	Max Power (kW)	Notes
Alpitronic	HYC400-2	Hypercharger	DC	200	1-4 Ports
Alpitronic	HYC400-3	Hypercharger	DC	300	1-4 Ports
Alpitronic	HYC400-4	Hypercharger	DC	400	1-4 Ports
Autel	AC W12-L-4G	AC Elite	AC	12	Single Port ; OCPP Full Certificate with software version V1.13.97
Autel	DC HiPower	DC HiPower	DC	640	The DC HiPower has a power cabinet with dispenser set up. It comes in 320, 480, or 640kW options and can be purchased with 2, 4, 6, or 8 ports depending on the number of dispensers.
Autel	Maxi UW19C002	MaxiCharger AC Pro 80A	AC	19.2	Single port.
Autel	Maxi UW19CJ02	MaxiCharger AC 80A	AC	19.2	Single port.
Autel	Maxi UW19L002	MaxiCharger AC Pro 80A	AC	19.2	Single port.
Autel	Maxi UW19LJ02	MaxiCharger AC 80A	AC	19.2	Single port.
Autel	UF####101	AC Ultra	AC	19.2	Single Port or Dual Port
Autel	UF160A4001	Maxicharger DC Fast 160kW	DC	160	Single or dual port
Autel	UF180A4001	Maxicharger DC Fast 180kW	DC	180	Single or dual port
Autel	UF200A4001	Maxicharger DC Fast 200kW	DC	200	Single or dual port
Autel	UF220A4001	Maxicharger DC Fast 220kW	DC	220	Single or dual port
Autel	UF240A4001	Maxicharger DC Fast 240kW	DC	240	Single or dual port
Blink	780	Series 7 ISO Single	AC	19.2	Single port.
Blink	01-0207-LTE (IQ 200 Advanced)	IQ 200 Advanced	AC	19.2	Single Port
Blink	01-0568	Blink 300kW	DC	300	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0569	Blink 360kW	DC	360	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0578	Blink 180kW	DC	180	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0581	Blink 240kW	DC	240	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	200-000320-A	Blink 200kW	DC	200	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	780 (40A)	Series 7 ISO (Enhanced)	AC	9.6	Dual Port, Standalone network capability
Blink	780 (48A)	Series 7 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability
Blink	780 Series	Series 7 ISO Plus	AC	19.2	Dual Port, Standalone network capability
Blink	880 (40A)	Series 8 ISO (Enhanced)	AC	9.6	Single or dual Port, Standalone network capability
Blink	880 (48A)	Series 8 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability
Blink	880 (80A)	Series 8 ISO Plus	AC	19.2	Dual Port, Standalone network capability
Blink	C50##### C80#####	C-Series	DC	600	Up to 8 ports. Kempower Power Unit supplies DC power to various distributed dispenser outputs including but not limited to the Kempower Satellite (offers single or dual port configurations), the Kempower Liquid Cooled Satellite, etc.. Details about qualifications relevant to each variant is detailed in the corresponding notes section.
BTC Power	HPCD6-500-05-005		DC	360	Can power up to 4 dual port Fleet Dispensers to 1 Power Cabinet and charge sequentially. can charge up to 8 vehicles sequentially as a result.
BTC Power	HPCT3-###-480-# / HPCD7-500-###-01#	Gen4 Public Dispenser	DC	360	Dual port.
CHAEVI	CV-3FD150P-IUL	SONIC (150kW)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD180P-IUL	SONIC (180kW)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3UD403P-NCC3	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
CHAEVI	DCV-3FD150-ICN	DUOCONIC (150kW)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	DCV-3FD180-ICN	DUOCONIC (180kW)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
Cyber Switching	CSE1-4G-BL	CSE1	AC	11.5	Single Port
Cyber Switching	CSE1-WIFI-BL	CSE1	AC	11.5	Single Port

Epic Charging	EC48-AC	Epic48	AC	11.5	Single Port, Standalone network capability
Epic Charging	EC80-AC	Epic80	AC	19.2	Single Port, Standalone network capability
EverCharge	EV002-48,E800-1000	EV02	AC	11.52	Single Port, Standalone network capability
EverCharge	EV002-48,E800-1000-40A	EV02	AC	8.3	Single Port, Standalone network capability
EverCharge	EV002-80,E800-1001	EV02	AC	19.2	Single Port, Standalone network capability
EverCharge	EV002-80,E800-1001-40A	EV02	AC	8.3	Single Port, Standalone network capability
EVSIS	JC-94F2-350-0T5	DC Charger 350kW	DC	350	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-94F2-400-0T5	DC Charger 400kW	DC	400	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-9932-180-CT	DC Charger 180kW	DC	180	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-9932-240-CT	DC Charger 240kW	DC	240	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
FLO	Ultra	Ultra	DC	320	Dual port.
Gravity	GR-LH500CX		DC	500	
Gravity	GT-AH200XX		DC	200	
Gravity	GT-AV200XX		DC	200	
Gravity	GT-LAV500EX		DC	500	
Gravity	GT-LLH500EX		DC	500	
Gravity	GT-LV500CX		DC	500	
Noodoe	AC11P/ AC11P Exceed		AC	11.5	Single port.
OpConnect	IC80	IC80	AC	19.2	Single Port NRTL Listed as EX-1193-1
OpConnect	SC80	SC80	AC	19.2	Single Port NRTL Listed as EX-1193-3
PowerPump	AC550	AC550	AC	10	Single Port.
Sinexcel	SEC1000/160Y-H-U ; SEC1000/160Y-T-U ; SEC1000/160Y-HH-U ; SEC1000/160Y-TT-U ; SEC1000/160Y-HT-U ; SEC1000/120Y-H-U ; SEC1000/120Y-T-U ; SEC1000/120Y-HH-U ; SEC1000/120Y-TT-U ; SEC1000/120Y-HT-U ; SEC1000/60Y-C-U ; SEC1000/60Y-S-U ; SEC1000/60Y-CC-U ; SEC1000/60Y-SS-U ; SEC1000/60Y-SC-U ;	SEC160	DC	160	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
Sinexcel	SEC1000/240Y-H-U SEC1000/240Y-HH-U SEC1000/240Y-HJ-U SEC1000/240Y-T-U SEC1000/240Y-HT-U SEC1000/240Y-TJ-U SEC1000/240Y-TT-U	SEC 240	DC	240	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
Sinexcel	SEC1000/360F-N-U SEC1000/480F-N-U SEC1000/200U-C-U SEC1000/200U-CC-U SEC1000/200U-CJ-U SEC1000/300U-H-U SEC1000/300U-HH-U SEC1000/300U-HC-U SEC1000/300U-HJ-U SEC1000/500U-F-U SEC1000/500U-FH-U SEC1000/500U-FC-U SEC1000/500U-FJ-U SEC1000/300U-T-U SEC1000/300U-TJ-U SEC1000/300U-HT-U SEC1000/300U-TT-U SEC1000/300U-TC-U SEC1000/500U-FT-U	SEC 480	DC	480	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Air cooling output 350A Liquid cooling sustained maximum output 500A
StarCharge	AC###AN030H####	Artemis	AC	19.2	Single port.
StarCharge	DC3200AN147XYZ/ DC2800AN147XYZ	Titan 320kW	DC	320	Dual port.
TurnOnGreen	EVP1100-W/CPEVAC-11KW-J17-WEVP		AC	11.4	Single Port
TurnOnGreen	EVP700-W/CPEVAC-7KW-J17-W/EVP70		AC	7.6	Single Port
Zerova	AXLU111001/AX48	AX48	AC	11	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
Zerova	AXLU191001/AX80	AX80	AC	19.1	Single Port, Standalone network capability
Zerova	DQWA242	DQ240	DC	240	Configurable to four or two cables
Zerova	DQWA360	DQ360	DC	360	Configurable to four or two cables
Zerova	DQWA482	DQ480	DC	480	Configurable to four or two cables
Zerova	DTWA240	DT240	DC	240	Configurable to four or two cables
Zerova	DZWU482	DZ480	DC	480	Configurable to two, four, or six cables

Fleet

Brand	Model	Model Name	Type	Max Power (kW)	Notes
Alpitronic	HYC400-1	Hypercharger	DC	100	1-4 Ports
Alpitronic	HYC400-2	Hypercharger	DC	200	1-4 Ports
Alpitronic	HYC400-3	Hypercharger	DC	300	1-4 Ports
Alpitronic	HYC400-4	Hypercharger	DC	400	1-4 Ports
Alpitronic	HYC50	Hypercharger	DC	50	1-2 Ports
Autel	AC W12-L-4G	AC Elite	AC	12	Single Port ; OCPP Full Certificate with software version V1.13.97
Autel	DC HiPower	DC HiPower	DC	640	The DC HiPower has a power cabinet with dispenser set up. It comes in 320, 480, or 640kW options and can be purchased with 2, 4, 6, or 8 ports depending on the number of dispensers.
Autel	MAXI US AC LW12	AC Lite	AC	12	Single port. NEMA 14-50 plug. Separate holster.
Autel	MAXI US AC W12	AC Elite Home	AC	12	Single port. NEMA 14-50 plug. Separate holster.
Autel	MAXI US AC W12-H	AC Elite Home	AC	12	Single port. NEMA 14-50 plug. Separate holster.
Autel	Maxi UW19C002	MaxiCharger AC Pro 80A	AC	19.2	Single port.
Autel	Maxi UW19CJ02	MaxiCharger AC 80A	AC	19.2	Single port.
Autel	Maxi UW19L002	MaxiCharger AC Pro 80A	AC	19.2	Single port.
Autel	Maxi UW19LB02	MaxiCharger AC 80A	AC	19.2	Single port.
Autel	Maxi UW19LJ02	MaxiCharger AC 80A	AC	19.2	Single port.
Autel	UF####001	AC Ultra	AC	19.2	Single Port or Dual Port. No credit card reader
Autel	UF####101	AC Ultra	AC	19.2	Single Port or Dual Port
Autel	UF060A3001	Maxicharger DC Fast 60kW	DC	60	Single or dual port
Autel	UF080A3001	Maxicharger DC Fast 80kW	DC	80	Single or dual port
Autel	UF100A3001	Maxicharger DC Fast 100kW	DC	100	Single or dual port
Autel	UF120A3001	Maxicharger DC Fast 120kW	DC	120	Single or dual port
Autel	UF140A4001	Maxicharger DC Fast 140kW	DC	140	Single or dual port
Autel	UF160A4001	Maxicharger DC Fast 160kW	DC	160	Single or dual port
Autel	UF180A4001	Maxicharger DC Fast 180kW	DC	180	Single or dual port
Autel	UF200A4001	Maxicharger DC Fast 200kW	DC	200	Single or dual port
Autel	UF220A4001	Maxicharger DC Fast 220kW	DC	220	Single or dual port
Autel	UF240A4001	Maxicharger DC Fast 240kW	DC	240	Single or dual port
Autel	UW12-J0610CA0002	MaxiCharger AC Single	AC	12	Single port.
Autel	UW12-J0650CA0002	MaxiCharger AC Single	AC	12	Single port.
Blink	780	Series 7 ISO Single	AC	19.2	Single port.
Blink	01-0202 (MQ 200)	MQ 200	AC	12	Single Port; NRTL listed as LiteOn MQW2-50C-M2-R#-#-23 and HQW2-50C-#-N#-#-23
Blink	01-0207-LTE (IQ 200 Advanced)	IQ 200 Advanced	AC	19.2	Single Port
Blink	01-0568	Blink 300kW	DC	300	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0569	Blink 360kW	DC	360	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0578	Blink 180kW	DC	180	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0581	Blink 240kW	DC	240	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	200-000320-A	Blink 200kW	DC	200	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	780 (40A)	Series 7 ISO (Enhanced)	AC	9.6	Dual Port, Standalone network capability
Blink	780 (48A)	Series 7 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability
Blink	780 Series	Series 7 ISO Plus	AC	19.2	Dual Port, Standalone network capability
Blink	880 (40A)	Series 8 ISO (Enhanced)	AC	9.6	Single or dual Port, Standalone network capability
Blink	880 (48A)	Series 8 ISO (Enhanced)	AC	11.52	Dual Port, Standalone network capability
Blink	880 (80A)	Series 8 ISO Plus	AC	19.2	Dual Port, Standalone network capability
Blink	C50##### C80#####	C-Series	DC	600	Up to 8 ports. Kempower Power Unit supplies DC power to various distributed dispenser outputs including but not limited to the Kempower Satellite (offers single or dual port configurations), the Kempower Liquid Cooled Satellite, etc.. Details about qualifications relevant to each variant is detailed in the corresponding notes section.
BTC Power	HPCD6-500-05-005		DC	360	Can power up to 4 dual port Fleet Dispensers to 1 Power Cabinet and charge sequentially. can charge up to 8 vehicles sequentially as a result.
BTC Power	HPCT3-###-480-# / HPCD7-500-###-01#	Gen4 Public Dispenser	DC	360	Dual port.
CHAEVI	CV-3FD120P-IUL	SONIC (120kW)	DC	120	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD150P-IUL	SONIC (150kW)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD180P-IUL	SONIC (180kW)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3UD403P-NCC3	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
CHAEVI	DCV-3FD120-ICN	DUOCONIC (120kW)	DC	120	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	DCV-3FD150-ICN	DUOCONIC (150kW)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	DCV-3FD180-ICN	DUOCONIC (180kW)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available

Cyber Switching	CSE1-4G-BL	CSE1	AC	11.5	Single Port
Cyber Switching	CSE1-WIFI-BL	CSE1	AC	11.5	Single Port
EnergiSpot	ATLEU2-50AAS	Level 2 AC Charger	AC	12	Single port per unit, when configured as a dual unit on a single pedestal, each charger delivers their perscribed max output rating - never splitting power on a simultaneous charging session.
EnergiSpot	ATLEU2-80AAS	Level 2 AC Charger	AC	19.2	Single port per unit, when configured as a dual unit on a single pedestal, each charger delivers their perscribed max output rating - never splitting power on a simultaneous charging session.
EnergiSpot	ATLUE2-32AAS	Level 2 AC Charger	AC	7.7	Single port per unit, when configured as a dual unit on a single pedestal, each charger delivers their perscribed max output rating - never splitting power on a simultaneous charging session.
Epic Charging	EC48-AC	Epic48	AC	11.5	Single Port, Standalone network capability
Epic Charging	EC80-AC	Epic80	AC	19.2	Single Port, Standalone network capability
Epic Charging	ECB48-AC	Epic48	AC	11.5	Single Port, Standalone network capability
Epic Charging	ECB80-AC	Epic80	AC	19.2	Single Port, Standalone network capability
EV Bolt	EV8-AC-PAX19	Prestige 19	AC	19.1	Single Port, Standalone network capability
EverCharge	EV002-48,E800-1000	EV02	AC	11.52	Single Port, Standalone network capability
EverCharge	EV002-48,E800-1000-40A	EV02	AC	8.3	Single Port, Standalone network capability
EverCharge	EV002-80,E800-1001	EV02	AC	19.2	Single Port, Standalone network capability
EverCharge	EV002-80,E800-1001-40A	EV02	AC	8.3	Single Port, Standalone network capability
EvoCharge	EVC5001####	EVC5001####	AC	12	Single port.
EvoCharge	EVO32-310-001	iEVSE Plus 32	AC	7.7	Single Port, Standalone network capability
EvoCharge	EVO32-310-002	iEVSE Plus 32	AC	7.7	Dual Port, Standalone network capability
EvoCharge	EVO32-320-001	iEVSE 32	AC	7.7	Single Port, Standalone network capability
EvoCharge	EVO32-320-002	iEVSE 32	AC	7.7	Dual Port, Standalone network capability
EvoCharge	EVO80-###-###	MAX80	AC	19.2	
EvoCharge	W1-1962-####	iEVSE	AC	9.6	
EV SIS	JC-94F2-350-0T5	DC Charger 350kW	DC	350	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EV SIS	JC-94F2-400-0T5	DC Charger 400kW	DC	400	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EV SIS	JC-9932-100-CT	DC Charger 100kW	DC	100	CCS/CHAdemo (optional), OCPP 2.0.1 will be supported
EV SIS	JC-9932-180-CT	DC Charger 180kW	DC	180	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EV SIS	JC-9932-240-CT	DC Charger 240kW	DC	240	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
FLO	CoRe+ MAX	CoRe+™ MAX	AC	19.2	Single Port
FLO	CoRe+ STD 21 FT	CoRe+™	AC	7.2	Dual Port , Standalone network capability
FLO	SmartTWO	SmartTWO™ Series	AC	7.2	Single Port, Standalone network capability
FLO	SmartTWO Cellular	SmartTWO™ Series	AC	7.2	Single Port, Standalone network capability
FLO	SmartTWO For City Curbside	SmartTWO™ Series	AC	7.2	Single Port, Standalone network capability
FLO	Ultra	Ultra	DC	320	Dual port.
Gravity	GR-LH500CX		DC	500	
Gravity	GT-AH200XX		DC	200	
Gravity	GT-AV200XX		DC	200	
Gravity	GT-LAV500EX		DC	500	
Gravity	GT-LLH500EX		DC	500	
Gravity	GT-LV500CX		DC	500	
Noodoe	AC11P/AC11P Exceed		AC	11.5	Single port.
OpConnect	IC80	IC80	AC	19.2	Single Port
OpConnect	OC-IC3-32AH		AC	7.2	NRTL Listed as EX-1193-1
OpConnect	OC-SC3-32AN		AC	7.7	Single Port, Standalone network capability
OpConnect	SC80	SC80	AC	19.2	Single Port
PowerPump	AC550	AC550	AC	10	NRTL Listed as EX-1193-3
Sinexcel	SEC1000/160Y-H-U ; SEC1000/160Y-T	SEC160	DC	160	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
Sinexcel	SEC1000/240Y-H-USEC1000/240Y-HH-I	SEC 240	DC	240	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A

					Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Air cooling output 350A Liquid cooling sustained maximum output 500A
Sinexcel	SEC1000/360F-N-USEC1000/480F-N-U	SEC 480	DC	480	
StarCharge	AC###AN030#####	Artemis	AC	19.2	Single port.
StarCharge	DC3200AN147XYZ/ DC2800AN147XYZ	Titan 320kW	DC	320	Dual port.
StarCharge	Neptune 240kW	Neptune 240kW	DC	240	OCA Full and Security certificates under software version 1.2009.0 (alternate company name on OCA cert - Wanbang Digital Energy Co., Ltd.)
TurnOnGreen	EVP1100-W/CPEVAC-11KW-J17-WEVP		AC	11.4	Single Port
TurnOnGreen	FSP1200/CPEVDC-120KW-#	FSP1200	DC	120	Single Port, CCS connector
TurnOnGreen	FSP600/CPEVDC-60KW-#	FSP600	DC	60	Single Port, CCS connector
Zerova	AXLU111001/AX48	AX48	AC	11	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
Zerova	AXLU191001/AX80	AX80	AC	19.1	Single Port, Standalone network capability
Zerova	DQWA242	DQ240	DC	240	Configurable to four or two cables
Zerova	DQWA360	DQ360	DC	360	Configurable to four or two cables
Zerova	DQWA482	DQ480	DC	480	Configurable to four or two cables
Zerova	DSWU122	ICS DS120	DC	120	1x CCS1 connector 1x CHAdeMO connector
Zerova	DSWU182	ICS DS180	DC	180	1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version V1.00
Zerova	DSWU601	ICS DS60	DC	60	1x CCS1 connector 1x CHAdeMO connector
Zerova	DSWU901		DC	90	1x CCS1 connector 1x CHAdeMO connector
Zerova	DTWA240	DT240	DC	240	Configurable to four or two cables
Zerova	DZWU482	DZ480	DC	480	Configurable to two, four, or six cables

Network - Fleet

Brand	Network	Notes
AmpUp	AmpUp	
Autel	Autel Cloud	OCPP Full certificate for software version 2.0.105
Blink	Blink Network	
CHAEVI	CHAEVI	
ChargeLab	ChargeLab	
Charli		
Charging	Charli Charging	
EV Connect	EVConnect	
EvoCharge	EvoCharge Network	
Gravity	Gravity Network	
Noodoe		OCPP Full certificate for software version v1.0.2
OpConnect	OpConnect Network	
PowerPump	PowerPump	

Network - Commercial

Brand	Network	Notes
AmpUp	AmpUp	
Autel	Autel Cloud	OCPP Full certificate for software version 2.0.105
Blink	Blink Network	
CHAEVI	CHAEVI	
ChargeLab	ChargeLab	
Charli		
Charging	Charli Charging	
EV Connect	EVConnect	
OpConnect	OpConnect Network	
PowerPump	PowerPump	